

GASOLINE PORTABLE SILENCED SERIES

AIR COOLED ENGINE 3000 RPM

Air Cooled

3000 rpm

LWA
2000/14/CE

HONDA



G S A

G T A

	MGTP 11 AE	MGTP 12 AE 3F
Code	PP79-11MSO	PP80-12TSO
On board control panel equipped with:		
	<ul style="list-style-type: none"> - DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency Stop - Soundproof canopy - Exhaust gas silencer - 2x32A 1ph 230V EEC socket - 1x16A 1ph 230V EEC socket 	<ul style="list-style-type: none"> - DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency Stop - Soundproof canopy - Exhaust gas silencer - 1x 16A 3Ph 400V EEC socket - 1x 32A 1Ph 230V EEC socket - 1x 16A 1Ph 230V EEC socket
Generator		
Type	Linz E1C11M B	Linz E1S11M AS
Power	11 kVA 230V	12 kVA 400V
Frequency	50 Hz	50 Hz
Engine		
Engine type	HONDA GX630	HONDA GX630
N° cylinders	2	2
Power	20,8 HP	20,8 HP
Engine speed	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline
Starting system	Electric	Electric
Dimensions & weight		
Fuel tank capacity	21 lt	21 lt
Running Time	4,4 hrs	4,4 hrs
Dry weight	204 Kg	204 Kg
Dimensions (L. x W. x H.)	970 x 600 x 750 mm	970 x 600 x 750 mm

Options

- Site tow trailer
- ≡● Road tow trailer
- Trolley

Legend

G	Gasoline	S	Single phase	A	Air cooled
D	Diesel	T	Three phase	W	Water cooled

TEKNO PROGET
Generators & Welders

27030 Villanova D'Ardenghi (PV) Italy • Via Roma 6
Tel. +39 02 942 1464 - Sales Dept. +39 0382 406 252

www.teknoproget.com
info@teknoproget.com

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.